## NSN 5306-00-616-2945

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-616-2945 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.374 inches and 0.453 inches **Fastener Length:** Between 0.765 inches and 0.812 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches **Grip Diameter:** Between 0.1889 inches and 0.1894 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.359 inches and 0.391 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Surface Finish:** 63.0 microinches grip Material: Steel comp 431 **Material Specification:** Mil-s-18732 military specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unf Shelf Life: e:

| N/a               |
|-------------------|
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
|                   |
|                   |

## NSN 5306-00-616-2945

Close Tolerance Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-18732 spec.