## NSN 5306-00-616-3660

Internal Wrenching Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-616-3660

View Online at https://aerobasegroup.com/nsn/5306-00-616-3660
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.662 inches and 0.712 inches
Fastener Length:
Between 4.047 inches and 4.077 inches
Head Diameter:
Between 0.639 inches and 0.649 inches
Head Height:
0.375 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.375 inches
Width Across Flats:
Between 0.313 inches and 0.315 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
34.0 rockwell c and 40.0 rockwell c
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

## NSN 5306-00-616-3660

Internal Wrenching Bolt - Page 2 of 2

## Mil-std (military Standard):

Mil-s-5626 spec.

