Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-616-3721



Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.625 inches and 0.703 inches

Fastener Length:

Between 1.203 inches and 1.250 inches

Head Style:

Hexagon

Head Height:

Between 0.234 inches and 0.266 inches

Width Between Flats:

Between 0.615 inches and 0.627 inches

Thread Diameter:

0.438 inches

Grip Length:

Between 0.547 inches and 0.578 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

20

Min. Tensile Strength (psi):

62000 pounds per square inch

Material:

Aluminum alloy

Material Specification:

Qq-a-200 federal specification single material response or qq-a-225 federal specification single material response or qq-a-430 federal

specification single material response

Surface Treatment:

Oxide film and anodize

Surface Treatment Specification:

Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

NSN 5306-00-616-3721

Machine Bolt - Page 2 of 2

Mil-std (military Standard):

Mil-c-5541 spec.

