NSN 5306-00-616-5648

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-616-5648 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.880 inches **Fastener Length:** 1.500 inches **Head Style:** Double hexagon extended washer **Head Height:** Between 0.430 inches and 0.437 inches Width Between Flats: Between 0.432 inches and 0.440 inches **Extended Washer Diameter:** Between 0.644 inches and 0.654 inches **Extended Washer Thickness:** Between 0.147 inches and 0.155 inches **First Diameter From Head:** Between 0.352 inches and 0.355 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.620 inches **Thread Diameter:** 0.438 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 170000 pounds per square inch **Hardness Rating:** 36.0 rockwell c Minimum Yield Strength: 140000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 4037 or steel comp 4042 **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

-

NSN 5306-00-616-5648

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0