# NSN 5306-00-616-8095

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-616-8095

**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

0.656 inches

## Fastener Length:

2.468 inches

#### Head Style:

Hexagon

Head Height:

0.250 inches

#### Width Between Flats:

Between 0.615 inches and 0.627 inches

#### Grip Diameter:

Between 0.4358 inches and 0.4367 inches

## Single Shear Strength:

14300 pounds per square inch

#### Thread Diameter:

0.437 inches

## Grip Length:

1.812 inches

## Thready Qty Per Inch (tpi):

20

## Min. Tensile Strength (psi):

160000 pounds per square inch

## **Product Name:**

Navy special project

## Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

## Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

# Thread Series Designator:

Unf

Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5306-00-616-8095

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.

