NSN 5306-00-616-8852



Shear Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-616-8852 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.276 inches **Fastener Length:** Between 1.276 inches and 1.291 inches **Head Style:** Hexagon **Head Height:** Between 0.110 inches and 0.125 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Shank Unthreaded Hole Diameter:** 0.070 inches first hole and 0.080 inches first hole **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.000 inches and 1.010 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Distance From Head Largest Bearing Surface To Shank Hole Center: 1.159 inches first hole Material: Steel **Surface Treatment:** Cadmium **Thread Series Designator:** Unf **Specification Data:** 80205-nas1103 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5306-00-616-8852

Shear Bolt - Page 2 of 2



Fiig:

A003b0