NSN 5306-00-619-4706

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-619-4706

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.750 inches |
| Fastener Length: |
| 3.250 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.250 inches |
| Width Between Flats: |
| Between 0.430 inches and 0.439 inches |
| Hole Diameter: |
| 0.070 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 2.500 inches |
| Hole Quantity: |
| 6 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Hole Configuration Style: |
| Hexagon longitudinal hole |
| Surface Finish: |
| |
| 63.0 microinches grip |
| 63.0 microinches grip Material: |
| Material: |
| Material: Steel comp 8740 |
| Material: Steel comp 8740 Material Specification: |
| Material: Steel comp 8740 |
| Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response |

Surface Treatment Specification:

Ams 2400 assn standard single treatment response

NSN 5306-00-619-4706

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

