

View Online at <https://aerobasegroup.com/nsn/5306-00-619-5811>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.382 inches

Fastener Length:

6.882 inches

Head Style:

Double hexagon w/hole

Head Height:

0.923 inches

Width Between Flats:

Between 1.056 inches and 1.066 inches

Extended Washer Diameter:

1.620 inches

Extended Washer Thickness:

0.222 inches

Grip Diameter:

Between 0.9980 inches and 0.9990 inches

Thread Diameter:

1.000 inches

Grip Length:

5.500 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response or ams 6300 assn standard 6th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Uns

Specification Data:

80205-nas636 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.