## NSN 5306-00-619-5949

Machine Bolt - Page 1 of 2

**Thread Class:** 

View Online at https://aerobasegroup.com/nsn/5306-00-619-5949



## 3a **Thread Direction: Right-hand Thread Length:** Between 0.600 inches and 0.640 inches Fastener Length: Between 0.720 inches and 0.760 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.300 inches and 0.340 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.420 inches and 0.460 inches **Extended Washer Thickness:** Between 0.040 inches and 0.080 inches Hole Diameter: 0.070 inches **Thread Diameter:** 0.250 inches Grip Length: 0.120 inches **Hole Quantity:** 4 Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Hardness Rating: 42.0 rockwell c and 46.0 rockwell c Hole Configuration Style: Double hexagon longitudinal hole Surface Finish: 63.0 microinches grip Material: Steel **Material Specification:**

C50t22 fscm 07482 mfr ref single material response

## NSN 5306-00-619-5949

Machine Bolt - Page 2 of 2

AeroBase Group

Precious Material:

Silver

Surface Treatment:

Silver

Surface Treatment Specification:

Ams 2410 assn standard single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0