## NSN 5306-00-620-2912



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-620-2912 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.437 inches and 0.516 inches **Fastener Length:** Between 0.765 inches and 0.812 inches **Head Style:** Hexagon **Head Height:** Between 0.140 inches and 0.172 inches Width Between Flats: Between 0.428 inches and 0.440 inches **Locking Feature:** Pellet threads **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.296 inches and 0.328 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Material: Steel comp 4140 fastener or steel comp 8740 fastener or steel comp 8630 fastener or steel comp 8735 fastener or steel comp 4130 fastener or steel comp 4037 fastener **Material Specification:** Mil-s-5626 military specification 1st material response fastener or mil-s-6049 military specification 2nd material response fastener or mil-s-6050 military specification 3rd material response fastener or mil-s-6098 military specification 4th material response fastener or mil-s-6758 military specification 5th material response fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response fastener **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Fiig:

No

Demilitarization:

## NSN 5306-00-620-2912

Machine Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.