

View Online at <https://aerobasegroup.com/nsn/5306-00-620-3316>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.991 inches and 1.011 inches

Fastener Length:

9.282 inches

Head Style:

Round w/wrench flats

Head Diameter:

1.375 inches

Head Height:

0.406 inches

Width Between Flats:

1.125 inches

Grip Diameter:

Between 0.8730 inches and 0.8737 inches

Shank Unthreaded Hole Diameter:

0.127 inches first hole and 0.134 inches first hole

Thread Diameter:

0.875 inches

Grip Length:

Between 8.271 inches and 8.291 inches

Thready Qty Per Inch (tpi):

14

Min. Tensile Strength (psi):

220000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

9.090 inches first hole

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0