

View Online at <https://aerobasegroup.com/nsn/5306-00-622-8629>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.937 inches

Fastener Length:

Between 1.923 inches and 1.953 inches

Head Style:

Bevel-conical

Head Diameter:

Between 0.988 inches and 1.000 inches

Head Height:

Between 0.585 inches and 0.605 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.146 inches first hole

Internal Drive Style:

Hexagon

Thread Diameter:

0.625 inches

Width Across Flats:

Between 0.563 inches and 0.567 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.750 inches first hole

Material:

Steel comp 3130 or steel comp 3140

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas150 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0