

View Online at <https://aerobasegroup.com/nsn/5306-00-624-0257>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.500 inches and 1.688 inches

Fastener Length:

Between 5.656 inches and 5.750 inches

Head Style:

Hexagon

Head Height:

Between 0.378 inches and 0.403 inches

Width Between Flats:

Between 0.922 inches and 0.938 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole and 0.016 inches first hole

Thread Diameter:

0.625 inches

Grip Length:

Between 3.684 inches and 4.156 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

18

Distance From Head Largest Bearing Surface To Shank Hole Center:

5.375 inches first hole

Material:

Steel comp 1016 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1022 or steel comp 1025 or steel comp 1017 or steel comp 1023

Material Specification:

Qq-s-637 federal specification 1st material response or qq-s-637 federal specification 2nd material response or qq-s-637 federal specification 3rd material response or astm a108 assn standard 4th material response or astm a108 assn standard 5th material response or astm a576 assn standard 6th material response or astm a108 assn standard 7th material response or astm a108 assn standard 8th material response or astm a108 assn standard 9th material response or astm a576 assn standard 10th material response

Surface Treatment:

Cadmium or chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 2 federal specification all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Fig:

A003b0