

View Online at <https://aerobasegroup.com/nsn/5306-00-625-2086>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

1.625 inches

Fastener Length:

3.125 inches

Head Style:

Flat chamfer

Head Diameter:

1.125 inches

Head Height:

0.312 inches

Shoulder Diameter:

0.835 inches first shoulder and 0.840 inches first shoulder

Shoulder Length:

0.844 inches first shoulder

Rib Major Diameter:

Between 0.870 inches and 0.880 inches

Rib Length:

Between 0.719 inches and 0.781 inches

Distance From Largest Diameter Of Bearing Surface Of Head To Ribs:

Between 0.062 inches and 0.125 inches

Thread Diameter:

0.750 inches

Features Provided:

Casehardened

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

114000 pounds per square inch

Hardness Rating:

21.0 rockwell c and 30.0 rockwell c

Shoulder Shape:

Ribbed first shoulder

Material:

Steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp 1040

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0