

View Online at <https://aerobasegroup.com/nsn/5306-00-625-5816>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 3.188 inches and 3.281 inches

Fastener Length:

Between 3.250 inches and 3.312 inches

Head Style:

Crowned hexagon

Head Height:

Between 0.193 inches and 0.213 inches

Width Between Flats:

Between 0.553 inches and 0.565 inches

Thread Diameter:

0.375 inches

Grip Length:

Between 0.031 inches and 0.062 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Material:

Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s 6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response or ams 6300 assn standard 6th material response

Surface Treatment:

Cadmium or chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification all treatment responses

Thread Series Designator:

Unf

Specification Data:

80205-nas428 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.