## NSN 5306-00-626-3843

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-626-3843 **Thread Direction:** Right-hand Thread Length: 0.510 inches **Fastener Length:** 0.920 inches **Head Style:** Hexagon extended washer **Head Height:** 0.440 inches Width Between Flats: 0.500 inches **Extended Washer Diameter:** Between 0.708 inches and 0.712 inches **Extended Washer Thickness:** 0.133 inches **Hole Diameter:** 0.062 inches **First Diameter From Head:** Between 0.338 inches and 0.342 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.410 inches **Thread Diameter:** 0.438 inches **Hole Quantity:** 6 **Hole Type:** Drilled **Nonstandard Thread Pitch Diameter:** +0.4024/+0.4045 inches Thready Qty Per Inch (tpi): Hardness Rating: 32.0 rockwell c and 36.0 rockwell c **Hole Configuration Style:** Round longitudinal hole **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 8740

**Material Specification:** 

Ams 6322 assn standard single material response

## NSN 5306-00-626-3843

Externally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0