

View Online at <https://aerobasegroup.com/nsn/5306-00-628-7973>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.710 inches

Fastener Length:

4.850 inches

Head Style:

Hexagon extended washer

Head Height:

0.054 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Extended Washer Diameter:

Between 1.052 inches and 1.062 inches

Extended Washer Thickness:

0.018 inches

First Diameter From Head:

0.655 inches

Second Diameter From Head:

Between 0.7545 inches and 0.7548 inches

Third Diameter From Head:

Between 0.660 inches and 0.662 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

1.500 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

2.540 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

4.130 inches

End Application:

Propeller systems

Thread Diameter:

0.750 inches

Thready Qty Per Inch (tpi):

16

Hardness Rating:

35.0 rockwell c and 40.0 rockwell c

Criticality Code Justification:

Agav and sftt

Externally Relieved Body Diameter Quantity:

3

Product Name:

Bolt-relieved spl

Special Features:

2 holes opposite end from head; countersunk to 0.22 diame

Material:

Stainless steel

Material Specification:

Ams6322 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type i class b per hs74 federal standard single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0