NSN 5306-00-629-3113

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-629-3113 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** 4.125 inches **Head Style:** Hexagon **Head Height:** 0.312 inches Width Between Flats: 1.500 inches **Shoulder Diameter:** 1.123 inches first shoulder and 1.124 inches first shoulder **Shoulder Length:** 1.812 inches first shoulder **Rib Major Diameter:** Between 1.130 inches and 1.135 inches Rib Length: 1.000 inches **Thread Diameter:** 1.000 inches Thready Qty Per Inch (tpi): 14 Hardness Rating: 30.0 rockwell c and 35.0 rockwell c **Shoulder Shape:** Ribbed first shoulder **Special Features:** Tapped hole in. Head 5/8-18 unf-2a by 1.062 in. Lg Material: Steel comp 1340 or steel comp 4140 or steel comp 8640 or steel comp 8740 **Material Specification:** Aisi assn standard all material responses or sae assn standard all material responses or 66 federal standard all material responses **Surface Treatment:** Zinc **Thread Series Designator:**

Shelf Life: N/a

Uns

NSN 5306-00-629-3113

Ribbed Shoulder Bolt - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0