## NSN 5306-00-630-4817

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-630-4817 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.372 inches and 0.422 inches **Fastener Length:** Between 1.257 inches and 1.287 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.265 inches and 0.285 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.340 inches and 0.350 inches **Extended Washer Thickness:** Between 0.054 inches and 0.074 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.865 inches and 0.885 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch Material: Steel **Material Specification:** 23-112, mcdonnel douglas corporation mfr ref single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5306-00-630-4817

Shear Bolt - Page 2 of 2



Fiig:

A003b0