## NSN 5306-00-632-2965

Machine Bolt - Page 1 of 2

**Thread Class:** 



View Online at https://aerobasegroup.com/nsn/5306-00-632-2965

Tilleau Class.
1a
Thread Direction:
Right-hand
Thread Length:
Between 0.410 inches and 0.450 inches
Fastener Length:
Between 0.560 inches and 0.580 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.320 inches and 0.340 inches
Width Between Flats:
Between 0.304 inches and 0.313 inches
Extended Washer Diameter:
Between 0.436 inches and 0.440 inches
Extended Washer Thickness:
Between 0.060 inches and 0.070 inches
Thread Diameter:
0.250 inches
Grip Length:
Between 0.130 inches and 0.150 inches
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
28
Surface Finish:
63.0 microinches grip
Material:
Steel
Material Specification:
C50t22, fscm 07482 mfr ref single material response
Surface Treatment:
Nickel
Surface Treatment Specification:
Ams 2403 assn standard single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
-

## NSN 5306-00-632-2965

Machine Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0