

View Online at <https://aerobasegroup.com/nsn/5306-00-633-0827>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.530 inches and 0.570 inches

**Fastener Length:**

Between 3.290 inches and 3.310 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.250 inches and 0.297 inches

**Width Between Flats:**

Between 0.740 inches and 0.750 inches

**Hole Diameter:**

0.070 inches

**First Diameter From Head:**

Between 0.495 inches and 0.499 inches

**Second Diameter From Head:**

Between 0.280 inches and 0.300 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.240 inches and 0.260 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

Between 2.740 inches and 2.760 inches

**Thread Diameter:**

0.375 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hole Configuration Style:**

Hexagon flats

**Externally Relieved Body Diameter Quantity:**

2

**Material:**

Steel comp 4140

**Surface Treatment:**

Cadmium

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0