

View Online at <https://aerobasegroup.com/nsn/5306-00-637-8688>

Thread Direction:

Right-hand

Thread Length:

Between 0.730 inches and 0.770 inches

Fastener Length:

Between 1.678 inches and 1.698 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.320 inches and 0.340 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

Hole Diameter:

0.062 inches

First Diameter From Head:

Between 0.218 inches and 0.228 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.928 inches and 0.948 inches

Thread Diameter:

0.250 inches

Hole Quantity:

4

Hole Type:

Drilled

Nonstandard Thread Pitch Diameter:

+0.2216/+0.2238 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Hole Configuration Style:

Hexagon longitudinal hole

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 601

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0