

View Online at <https://aerobasegroup.com/nsn/5306-00-637-9680>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.938 inches and 0.969 inches

**Fastener Length:**

1.000 inches

**Head Style:**

Crowned hexagon

**Head Height:**

0.172 inches

**Width Between Flats:**

0.500 inches

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.031 inches and 0.062 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Special Features:**

Supplied w/slot in end of shank

**Material:**

Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

**Material Specification:**

Mil-b-6812 military specification all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-b-6812 spec.