## NSN 5306-00-638-2630

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-638-2630 **Thread Direction:** Right-hand Thread Length: Between 0.615 inches and 0.695 inches **Fastener Length:** Between 0.990 inches and 1.010 inches **Head Style:** Hexagon **Head Height:** Between 0.146 inches and 0.166 inches Width Between Flats: Between 0.431 inches and 0.440 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.315 inches and 0.375 inches **Features Provided:** Finished head **Nonstandard Thread Pitch Diameter:** +0.2216/+0.2238 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 136000 pounds per square inch **Hardness Rating:** 30.0 rockwell c and 38.0 rockwell c Material: Steel comp 601 **Material Specification:** Ams 6304 assn standard single material response **Surface Treatment:** Nickel and cadmium **Surface Treatment Specification:** Ams 2416 assn standard all treatment responses **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## **NSN 5306-00-638-2630** Machine Bolt - Page 2 of 2



Fiig:

A003b0