## NSN 5306-00-638-2702

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-638-2702 **Thread Class:** 1a **Thread Direction:** Right-hand Thread Length: Between 0.875 inches and 0.938 inches **Fastener Length:** 1.125 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.375 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** 0.500 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.190 inches and 0.250 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 63.0 microinches grip Material: Iron alloy 660 **Material Specification:** Ams 5735 assn standard single material response **Thread Series Designator:** Unf Shelf Life: N/a

## NSN 5306-00-638-2702

Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0