## NSN 5306-00-638-3812



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-638-3812 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.490 inches and 0.520 inches **Fastener Length:** Between 1.260 inches and 1.270 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.360 inches and 0.400 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.480 inches and 0.520 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.750 inches and 0.770 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 24 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c Surface Finish: 63.0 microinches grip Material: Steel **Material Specification:** B50t12a pacific mercury electronics inc. Mfr ref single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** 

Unf

Shelf Life:

N/a

## NSN 5306-00-638-3812

Machine Bolt - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A003b0