

View Online at <https://aerobasegroup.com/nsn/5306-00-638-5555>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.550 inches and 0.576 inches

**Fastener Length:**

Between 0.700 inches and 0.720 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.240 inches and 0.260 inches

**Width Between Flats:**

Between 0.618 inches and 0.627 inches

**Shoulder Diameter:**

0.4330 inches first shoulder and 0.4370 inches first shoulder

**Shoulder Length:**

0.144 inches first shoulder and 0.150 inches first shoulder

**Hole Diameter:**

0.062 inches

**Thread Diameter:**

0.312 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Nonstandard Thread Pitch Diameter:**

+0.2800/+0.2824 inches

**Thready Qty Per Inch (tpi):**

24

**Hole Configuration Style:**

Hexagon flats

**Shoulder Shape:**

Round first shoulder

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0