NSN 5306-00-638-5816

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-638-5816

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.656 inches |
| Fastener Length: |
| 0.719 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.234 inches and 0.266 inches |
| Width Between Flats: |
| 0.625 inches |
| Shank Unthreaded Hole Diameter: |
| 0.106 inches first hole |
| Thread Diameter: |
| 0.438 inches |
| Grip Length: |
| 0.063 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 125000 pounds per square inch |
| Hardness Rating: |
| 26.0 rockwell c and 32.0 rockwell c |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 0.547 inches first hole |
| Product Name: |
| Bolt, machine |
| Special Features: |
| 1 drilled hole |
| Material: |
| Steel |
| Surface Treatment: |
| Cadmium |
| Thread Series Designator: Unf |
| Ont Shelf Life: |
| N/a |
| IN/a |

NSN 5306-00-638-5816

Machine Bolt - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

