NSN 5306-00-638-7656

Machine Bolt - Page 1 of 2

Between 0.294 inches and 0.365 inches

Thread Direction:

Thread Length:

Fastener Length:

Right-hand



View Online at https://aerobasegroup.com/nsn/5306-00-638-7656

rasteller Leligtii.
Between 0.365 inches and 0.368 inches
Head Style:
Hexagon
Head Height:
Between 0.240 inches and 0.260 inches
Width Between Flats:
Between 0.430 inches and 0.439 inches
Hole Diameter:
0.068 inches
Thread Diameter:
0.250 inches
Hole Quantity:
6
Hole Type:
Drilled
Features Provided:
Finished head
Nonstandard Thread Pitch Diameter:
+0.2213/+0.2238 inches
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 28
28
28 Hardness Rating:
28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c
28 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style:
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish:
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head Material:
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 601
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 601 Material Specification:
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment:
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium Surface Treatment Specification:
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium Surface Treatment Specification: Ams 2416 assn standard all treatment responses
Hardness Rating: 30.0 rockwell c and 38.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Surface Finish: 63.0 microinches bearing surface of head Material: Steel comp 601 Material Specification: Ams 6304 assn standard single material response Surface Treatment: Nickel and cadmium Surface Treatment Specification: Ams 2416 assn standard all treatment responses Thread Series Designator:

NSN 5306-00-638-7656

Machine Bolt - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0