NSN 5306-00-638-7657

Machine Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-00-638-7657 |
|---|
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.678 inches |
| Fastener Length: |
| Between 0.678 inches and 0.698 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| Between 0.334 inches and 0.354 inches |
| Width Between Flats: |
| Between 0.362 inches and 0.377 inches |
| Extended Washer Diameter: |
| Between 0.490 inches and 0.510 inches |
| Extended Washer Thickness: |
| Between 0.070 inches and 0.090 inches |
| Hole Diameter: |
| 0.070 inches |
| Thread Diameter: |
| 0.312 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Nonstandard Thread Pitch Diameter: |
| +0.2797/+0.2824 inches |
| Thready Qty Per Inch (tpi): |
| 24 |
| Hardness Rating: |
| 30.0 rockwell c and 38.0 rockwell c |
| Hole Configuration Style: |
| Round |
| Surface Finish: |
| 63.0 microinches bearing surface of head |
| Material: |
| Steel comp 601 |
| Material Specification: |
| Ams 6304 assn standard single material response |

Surface Treatment:

Nickel and cadmium

NSN 5306-00-638-7657

Machine Bolt - Page 2 of 2



Ams 2416 assn standard all treatment responses

Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0