## NSN 5306-00-638-8263

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-638-8263 **Thread Class:** 1a **Thread Direction:** Right-hand Thread Length: Between 0.653 inches and 0.693 inches **Fastener Length:** Between 3.053 inches and 3.073 inches **Head Style:** Hexagon **Head Height:** Between 0.209 inches and 0.229 inches Width Between Flats: Between 0.553 inches and 0.564 inches **First Diameter From Head:** Between 0.3738 inches and 0.3748 inches **Second Diameter From Head:** Between 0.315 inches and 0.325 inches Third Diameter From Head: Between 0.3738 inches and 0.3743 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.490 inches and 0.510 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.890 inches and 1.910 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 2.380 inches and 2.400 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 30.0 rockwell c and 38.0 rockwell c **Externally Relieved Body Diameter Quantity:** 3 Material: Stainless steel **Material Specification:** Ams 5616 assn standard single material response **Thread Series Designator:** 

Thread Set Unf Shelf Life: N/a

## NSN 5306-00-638-8263

Externally Relieved Body Bolt - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0