NSN 5306-00-639-1719



Internal Wrenching Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-639-1719 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.787 inches and 0.837 inches **Fastener Length:** Between 2.173 inches and 2.203 inches **Head Diameter:** Between 0.818 inches and 0.828 inches **Head Height:** 0.500 inches **Hole Diameter:** 0.055 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.375 inches and 0.378 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 34.0 rockwell c and 40.0 rockwell c Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:**

Shelf Life: N/a

Unf

Thread Series Designator:

Qq-p-416, type 2 cl 2 federal specification single treatment response

NSN 5306-00-639-1719

Internal Wrenching Bolt - Page 2 of 2



Unit Of Mea	sure:
-------------	-------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.