

View Online at <https://aerobasegroup.com/nsn/5306-00-639-2507>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.500 inches

Fastener Length:

2.188 inches

Head Style:

Hexagon

Head Height:

0.281 inches

Width Between Flats:

0.875 inches

Grip Diameter:

0.5616 inches

Shank Unthreaded Hole Diameter:

0.141 inches first hole

Single Shear Strength:

23600 pounds per square inch

Thread Diameter:

0.562 inches

Grip Length:

1.688 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.000 inches first hole

Material:

Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response or mil-s-8695 military specification 6th material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.