

View Online at <https://aerobasegroup.com/nsn/5306-00-639-3017>

Thread Direction:

Right-hand

Thread Length:

0.287 inches

Fastener Length:

Between 1.780 inches and 1.800 inches

Head Style:

Hexagon

Head Height:

Between 0.110 inches and 0.130 inches

Width Between Flats:

Between 0.493 inches and 0.502 inches

Shoulder Diameter:

0.3715 inches first shoulder and 0.3730 inches first shoulder

Shoulder Length:

1.509 inches first shoulder and 1.513 inches first shoulder

Shank Unthreaded Hole Diameter:

0.062 inches first hole and 0.065 inches first hole

Thread Diameter:

0.250 inches

Nonstandard Thread Pitch Diameter:

+0.2213/+0.2238 inches

Thready Qty Per Inch (tpi):

28

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.712 inches first hole and 1.720 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Stainless steel

Precious Material:

Silver

Surface Treatment:

Silver

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0