NSN 5306-00-639-6852

Machine Bolt - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5306-00-639-6852

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.350 inches |
| Fastener Length: |
| 0.750 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| 0.110 inches |
| Width Between Flats: |
| 0.370 inches |
| Shank Unthreaded Hole Diameter: |
| 0.082 inches first hole |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| 0.400 inches |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Hardness Rating: |
| 37.0 rockwell b |
| Minimum Yield Strength: |
| 110000 pounds per square inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 0.610 inches first hole |
| Material: |
| Steel |
| Material Specification: |
| Ams 5667 assn standard single material response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 5306-00-639-6852 Machine Bolt - Page 2 of 2



Fiig:

A003b0