NSN 5306-00-649-2253

View Online at https://aerobasegroup.com/nsn/5306-00-649-2253

Machine Bolt - Page 1 of 2



Thread Class: 1a **Thread Direction:** Right-hand Thread Length: Between 0.650 inches and 0.690 inches **Fastener Length:** Between 1.050 inches and 1.070 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.360 inches and 0.380 inches Width Between Flats: Between 0.367 inches and 0.375 inches **Extended Washer Diameter:** Between 0.470 inches and 0.490 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Hole Diameter:** 0.070 inches **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.380 inches and 0.400 inches **Hole Quantity:** 2 **Hole Type:** Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): **Hole Configuration Style:** Hexagon flats Material: Steel **Material Specification:** C50t22, general electric co. Mfr ref single material response **Surface Treatment:** Nickel

Ams 2403 assn standard single treatment response

Surface Treatment Specification:

NSN 5306-00-649-2253

Machine Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:

Unit Of Measure:

__

N/a

Demilitarization:

No

Fiig:

A003b0