

View Online at <https://aerobasegroup.com/nsn/5306-00-652-5558>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.969 inches

**Fastener Length:**

4.875 inches

**Head Style:**

Round w/wrench flats

**Head Diameter:**

0.938 inches

**Head Height:**

0.250 inches

**Width Between Flats:**

0.812 inches

**Shoulder Diameter:**

0.617 inches first shoulder and 0.622 inches first shoulder

**Shoulder Length:**

4.047 inches first shoulder and 4.062 inches first shoulder

**Shank Unthreaded Hole Diameter:**

0.140 inches first hole

**Thread Diameter:**

0.562 inches

**Thready Qty Per Inch (tpi):**

18

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.641 inches first hole and 4.656 inches first hole

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1524 or steel comp 1025

**Material Specification:**

Qq-s-633 canc federal specification all material responses

**Surface Treatment:**

Phosphate

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0