## NSN 5306-00-655-5759

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-655-5759 **Thread Direction:** Right-hand Thread Length: Between 0.390 inches and 0.410 inches **Fastener Length:** Between 1.288 inches and 1.340 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.250 inches and 0.270 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Shoulder Diameter:** 0.245 inches first shoulder and 0.247 inches first shoulder **Shoulder Length:** 0.820 inches first shoulder and 0.840 inches first shoulder **Thread Diameter:** 0.190 inches **Nonstandard Thread Pitch Diameter:** +0.1644/+0.1667 inches Thready Qty Per Inch (tpi): 32 **Hardness Rating:** 80.0 rockwell superficial 15-n grip **Shoulder Shape:** Round first shoulder Material: Stainless steel **Material Specification:** B50t12a fscm 07482 mfr ref single material response **Thread Series Designator:** Uns Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## **NSN 5306-00-655-5759** Shoulder Bolt - Page 2 of 2



Fiig:

A003b0