## NSN 5306-00-655-7447

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-655-7447 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.406 inches **Fastener Length:** 1.031 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches **Grip Diameter:** Between 0.1889 inches and 0.1894 inches **Thread Diameter:** 0.1904 inches **Grip Length:** 0.625 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch **Surface Finish:** 63.0 microinches grip Material: Aluminum or aluminum alloy 2024 or aluminum alloy 1100 or aluminum alloy 2017 or aluminum alloy 2024 or aluminum alloy 2117 or aluminum alloy 5056 **Surface Treatment:** Oxide film and anodize **Surface Treatment Specification:** Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

Fiig: A003b0

No

**Demilitarization:** 

## NSN 5306-00-655-7447

Close Tolerance Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-c-5541 spec.