

View Online at <https://aerobasegroup.com/nsn/5306-00-655-9954>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.469 inches

Eye Inside Diameter:

Between 0.190 inches and 0.192 inches

Shoulder Thickness:

0.078 inches

Shank Length:

Between 5.516 inches and 5.562 inches

Eye Stock Thickness:

Between 0.120 inches and 0.130 inches

Shoulder Diameter:

0.500 inches

Overall Length:

6.280 inches

Thread Diameter:

0.250 inches

Features Provided:

Casehardened

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Eye Outside Width:

0.500 inches

Material:

Steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-6050 military specification 2nd material response or mil-s-6098 military specification 3rd material response or mil-s-6049 military specification 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty2, cl 3 federal specification single treatment response

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.