

View Online at <https://aerobasegroup.com/nsn/5306-00-674-9016>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.284 inches

**Fastener Length:**

1.925 inches

**Head Style:**

Hexagon

**Head Height:**

0.200 inches

**Width Between Flats:**

0.625 inches

**First Diameter From Head:**

Between 0.4998 inches and 0.5001 inches

**Second Diameter From Head:**

Between 0.3746 inches and 0.3748 inches

**Third Diameter From Head:**

0.312 inches

**Fourth Diameter From Head:**

Between 0.3746 inches and 0.3748 inches

**Fifth Diameter From Head:**

0.238 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.050 inches

**Distance From Largest Bearing Surface Of Head To End Of Second Diameter:**

1.279 inches

**Distance From Largest Bearing Surface Of Head To End Of Third Diameter:**

1.435 inches

**Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter:**

1.500 inches

**Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter:**

1.641 inches

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

18

**Externally Relieved Body Diameter Quantity:**

5

**Material:**

Steel comp 303

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0