## NSN 5306-00-674-9246

Machine Bolt - Page 1 of 2

Between 0.184 inches and 0.260 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5306-00-674-9246

Between 0.240 inches and 0.260 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.223 inches and 0.243 inches
Width Between Flats:
Between 0.211 inches and 0.219 inches
Extended Washer Diameter:
Between 0.328 inches and 0.338 inches
Extended Washer Thickness:
Between 0.033 inches and 0.043 inches
Hole Diameter:
0.047 inches
Thread Diameter:
0.164 inches
Hole Quantity:
4
Hole Type:
Drilled
Features Provided:
Finished head
Thready Qty Per Inch (tpi):
36
Hardness Rating:
32.0 rockwell c and 36.0 rockwell c
Hole Configuration Style:
Double hexagon longitudinal hole
Surface Finish:
63.0 microinches bearing surface of head
Material:
Steel comp 601
Material Specification:
Ams 6304 assn standard single material response
Surface Treatment:
Nickel

## NSN 5306-00-674-9246

Machine Bolt - Page 2 of 2



•	_		_		
Siirtor	e Trea	tmani	· Sno	へけいひょ	otion:
Juliat	.6 1166		· JUE	<b>61116</b>	alivii.

Ams 2403 assn standard single treatment response or +16-te3e class a, fscm 99207 mfr ref single treatment response

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0