

View Online at <https://aerobasegroup.com/nsn/5306-00-674-9247>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.363 inches and 0.416 inches

Fastener Length:

Between 0.451 inches and 0.471 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.223 inches and 0.243 inches

Width Between Flats:

Between 0.211 inches and 0.219 inches

Extended Washer Diameter:

Between 0.328 inches and 0.338 inches

Extended Washer Thickness:

Between 0.033 inches and 0.043 inches

Hole Diameter:

0.047 inches

Thread Diameter:

0.164 inches

Grip Length:

Between 0.055 inches and 0.088 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

36

Hardness Rating:

32.0 rockwell c and 36.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

63.0 microinches bearing surface of head

Material:

Steel comp 601

Material Specification:

Ams 6304 assn standard single material response

Surface Treatment:

Nickel

Surface Treatment Specification:

Ams 2403 assn standard single treatment response or +16-te3e class a, fscm 99207 mfr ref single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0