

View Online at <https://aerobasegroup.com/nsn/5306-00-676-6288>

Thread Direction:

Right-hand

Thread Length:

0.270 inches

Fastener Length:

Between 0.760 inches and 0.780 inches

Head Style:

Hexagon

Head Height:

Between 0.115 inches and 0.135 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Shank Unthreaded Hole Diameter:

0.650 inches first hole and 0.670 inches first hole

Thread Diameter:

0.190 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Features Provided:

Finished head

Nonstandard Thread Pitch Diameter:

+0.1644/+0.1667 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

142000 pounds per square inch

Hardness Rating:

32.0 rockwell c and 38.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.065 inches first hole and 0.072 inches first hole

Material:

Stainless steel

Material Specification:

Ams 5616 assn standard single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0