

View Online at <https://aerobasegroup.com/nsn/5306-00-677-9843>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.850 inches and 0.970 inches

Eye Inside Diameter:

Between 0.500 inches and 0.510 inches

Shoulder Thickness:

Between 0.080 inches and 0.100 inches

Shank Length:

Between 1.180 inches and 1.240 inches

Eye Stock Thickness:

Between 0.360 inches and 0.400 inches

Shoulder Diameter:

Between 1.365 inches and 1.385 inches

Overall Length:

Between 2.830 inches and 3.010 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

150000 pounds per square inch

Distance From Center Of Eye To Shank End:

2.260 inches

Eye Outside Width:

Between 1.365 inches and 1.385 inches

Material:

Steel

Material Specification:

Mil-s-5626, physical cond d, surface cond 1 military specification single material response or mil-s-6758, physical cond d, surface cond 4 military specification single material response

Surface Treatment:

Cadmium

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.