NSN 5306-00-678-1412

Ribbed Shoulder Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-678-1412 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.780 inches **Fastener Length:** 3.620 inches **Head Height:** 0.250 inches Width Between Flats: 1.000 inches **Rib Major Diameter:** Between 0.820 inches and 0.825 inches Rib Length: 0.250 inches **Rib Quantity:** 25 **Thread Diameter:** 0.500 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 32.0 rockwell c and 38.0 rockwell c **Special Features:** 3rd shoulder round, 0.618 in. Min, 0.624 in. Maximum diameter by 1.320 in. Lg Material: Steel comp 4340 or steel comp 5140 or steel comp 8640 or steel comp 8740 or steel comp 8637 **Surface Treatment:** Cadmium or zinc **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification 1st treatment response or qq-z-325, type 2, cl 3 federal specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

No Fiig:

A003b0

Demilitarization: