NSN 5306-00-679-8109

Ribbed Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-679-8109

| TI 101 | | |
|--|--|--|
| Thread Class: | | |
| 2a | | |
| Thread Direction: | | |
| Right-hand | | |
| Thread Length: | | |
| Between 0.830 inches and 0.860 inches | | |
| Fastener Length: | | |
| Between 1.270 inches and 1.300 inches | | |
| Head Style: | | |
| Dee | | |
| Head Diameter: | | |
| 0.624 inches | | |
| Head Height: | | |
| 0.188 inches | | |
| Distance From Centerline To Flat: | | |
| Between 0.156 inches and 0.176 inches | | |
| Shoulder Diameter: | | |
| 0.303 inches first shoulder and 0.307 inches first shoulder | | |
| Shoulder Length: | | |
| 0.320 inches first shoulder | | |
| Rib Major Diameter: | | |
| Between 0.317 inches and 0.321 inches | | |
| Rib Length: | | |
| 0.260 inches | | |
| Distance From Largest Diameter Of Bearing Surface Of Head To Ribs: | | |
| Between 0.030 inches and 0.090 inches | | |
| Rib Minor Diameter: | | |
| Between 0.303 inches and 0.307 inches | | |
| Rib Quantity: | | |
| 33 | | |
| Thread Diameter: | | |
| 0.312 inches | | |
| Thready Qty Per Inch (tpi): | | |
| 24 | | |
| Hardness Rating: | | |
| 32.0 rockwell c and 36.0 rockwell c | | |
| Shoulder Shape: | | |
| Ribbed first shoulder | | |
| Material: | | |
| Steel comp 1335 or steel comp 1541 | | |

Material Specification:

Sae assn standard all material responses

NSN 5306-00-679-8109

Ribbed Shoulder Bolt - Page 2 of 2



| Thread | Series | Designator: |
|--------|--------|-------------|
|--------|--------|-------------|

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0