NSN 5306-00-680-5290

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-680-5290
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.562 inches
Fastener Length:
3.250 inches
Head Style:
Hexagon
Head Height:
0.375 inches
Width Between Flats:
1.062 inches
Grip Diameter:
0.7488 inches
Thread Diameter:
0.750 inches
Grip Length:
2.688 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Product Name:
Navy special project
Material:
Steel comp 4140 or steel comp e4340 or steel comp 6150 or steel comp 8735 or steel comp 8740 or steel comp 4037
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military
specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material
response or mil-s-8695 military specification 6th material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification all treatment responses
Thread Series Designator:
Un
Specification Data:
80205-nas464 professional/industrial association standard

N/a

Shelf Life:

NSN 5306-00-680-5290

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.