

NSN 5306-00-680-6914 Internally Relieved Body Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-680-6914 **Thread Class:** 1a **Thread Direction:** Right-hand Thread Length: Between 0.802 inches and 0.822 inches **Fastener Length:** Between 0.802 inches and 0.822 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **Hole Diameter:** 0.065 inches **Counterbore Diameter:** Between 0.196 inches and 0.216 inches **Counterbore Depth:** 

0.199 inches

**Concentric Hole Diameter:** 

Between 0.045 inches and 0.050 inches

**Thread Diameter:** 

0.312 inches

**Hole Quantity:** 

4

**Hole Type:** 

Thready Qty Per Inch (tpi):

24

**Hole Configuration Style:** 

Round

Material:

Iron alloy 660

**Material Specification:** 

Ams 5732 assn standard single material response

**Precious Material And Location:** 

silver

## **NSN 5306-00-680-6914**Internally Relieved Body Bolt - Page 2 of 2



Precious Material:	
Silver	
Surface Treatment:	
Silver	
Surface Treatment Specification:	
Ams 2410 assn standard single treatment response	
Style Designator:	
Counterbore unthreaded	
Thread Series Designator:	
Unf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	

A003b0