NSN 5306-00-682-6009

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-682-6009 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.782 inches **Fastener Length:** 2.844 inches **Head Style:** Hexagon **Head Height:** Between 0.265 inches and 0.297 inches Width Between Flats: Between 0.740 inches and 0.752 inches **End Application:** Spec item **Thread Diameter:** 0.500 inches **Grip Length:** 2.062 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 62000 pounds per square inch Material: Aluminum alloy 2024 or aluminum alloy **Material Specification:** Qq-a-267 federal specification 1st material response or qq-a-268 federal specification 1st material response or mil-w-7986 military specification 2nd material response **Surface Treatment:** Oxide film and anodize **Surface Treatment Specification:** Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response

Thread Series Designator: Unf Shelf Life: N/a **Unit Of Measure:** Demilitarization:

No

NSN 5306-00-682-6009

Machine Bolt - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-w-7986 spec.